

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
18 December 2003 (18.12.2003)


PCT

(10) International Publication Number  
WO 03/103929 A2

- (51) International Patent Classification<sup>7</sup>: B29C 65/00 (74) Agents: AGMON, Jonathan et al.; Soroker - Agmon, Advocates & Patent Attorneys, 12th floor, Levinstein Tower, 23 Petach Tikva Road, 66184 Tel Aviv (IL).
- (21) International Application Number: PCT/IL03/00476
- (22) International Filing Date: 4 June 2003 (04.06.2003) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/385,607 5 June 2002 (05.06.2002) US
- (71) Applicant (*for all designated States except US*): NOVA-TEK TECHNOLOGIES, LTD. [IL/IL]; P.O. Box 8389, Sapir Industrial Zone, IS-42504 Netanya (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): MATARARSSO, Hasdi [IL/IL]; 12 Amnon VeTamar Street, 42202 Netanya (IL).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: AN IMPROVED CELLULAR CUSHIONED MATERIAL



(57) Abstract: An inflatable cellular cushioning material having an air inlet pipe path to be inflated by an inflating device through the use of an air inlet pipe, the inflatable cushioning material comprising at least two layers of plastic pre-welded in such a manner so as to form a substantially diagonally oriented lines forming sleeves along the longitudinal axis of the inflatable cellular cushioning material and a substantially horizontal welded lines along the path of the air inlet pipe whereby the horizontal welded lines substantially reduce the non-inflated areas along the path of the air inlet pipe.

WO 03/103929 A2

WO 03/103929 A2



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## AN IMPROVED CELLULAR CUSHIONED MATERIAL

## PRIORITY APPLICATION

The present application claims priority from U.S. application  
5 60/385,607 titled DEVICE AND METHOD FOR THE PRODUCTION OF  
CELLULAR CUSHIONED MATERIAL filed on June 5, 2002.

## BACKGROUND OF THE INVENTION

## FIELD OF THE INVENTION

10 The present invention generally relates to an improved cellular  
cushioned material and to an improved pre-welded cellular cushioned material  
and a method for making the same in particular.

## DISCUSSION OF THE RELATED ART

15 Cellular cushioning material is used for packing and for the filling of  
empty volumes. U.S. Patent Application Serial number 09/758,544, publication  
serial number 2002/0094393A1 filed by Matarasso discloses a pre-welded  
cellular cushioning material and method, the method includes providing a pre-  
welded sheet to a user comprised of at least two layers of plastic pre-welded to  
20 have a plurality of diagonally oriented, inflatable sleeves extending substantially  
the entire width of said sheet, and a horizontally extending air entry passage.  
According to Matarasso each of the inflatable sleeves has an opening for allowing  
entry of air from said air entry passage into the sleeve. The user inflates the  
cellular cushioning material using an air injecting pipe located in the center of the  
25 sheet inflated, the pipe is inserted into the mid section of the plastic sheet using a  
knife for cutting a passageway in the middle or side section of the inflatable  
plastic sheet.

According to Matarasso each of the sleeves is welded from all sides  
except for a small opening. Once air is injected into the diagonal sleeves a

horizontal welding is applied to the plastic sheet. The longitudinal welding is applied to the inflated plastic sheet at predetermined intervals. The welding is applied using horizontal bars. Each weld slows down the production of the cellular cushioning material. Due to openings between the pre-welded sections  
5 entire areas juxtaposed to the air inlet pipe are not sealed from all of their sides causing a significant reduction in the efficiency of the partially inflated plastic sheet.

Reference is now made to Fig. 1 which shows a plastic sheet having a plurality of diagonally oriented, inflatable sleeves extending substantially the  
10 entire width of the shown sheet, known in the art. Once diagonal 100, 101, 102 are air filled, longitudinal weld 104 is made using horizontal welding bars, thus creating non-inflated area 108. Like non-inflated areas are located throughout the length of the air filling section of the plastic sheet. The longer the distance between longitudinal welds 104, 106 the larger the non-inflated section that is  
15 created within the plastic sheet.

It is therefore an object of the present invention to provide a pre-welded cellular cushioning material having a minimal non-inflated section.

It is also an object of the present invention to provide an additional horizontal weld during the process of longitudinal welding thus minimizing the  
20 non-inflated section during the production of the inflated cellular cushioning material.

## SUMMARY OF THE PRESENT INVENTION

In accordance with the above objects, the present invention provides a pre-welded cellular cushioning material.

According to one aspect of the present invention there is provided an inflatable cellular cushioning material having an air inlet pipe path to be inflated by an inflating device through the use of an air inlet pipe, the inflatable cushioning material comprising two or more layers of plastic pre-welded in such a manner so as to form a substantially diagonally oriented lines forming sleeves or cell structure along the longitudinal axis of the inflatable cellular cushioning material and a substantially longitudinal welded lines along the path of the air inlet pipe, the longitudinal welded lines have non-welded longitudinal line areas to allow for the inflating of the sleeves or cell structure, whereby the longitudinal welded lines substantially reduce the non-inflated areas along the path of the air inlet pipe. The longitudinal welded lines are pre-welded before the plastic sheet is inflated by the inflating device or are welded after the sleeves have been inflated. Alternatively, the longitudinal welded lines are welded using an L shaped plastic sealing bars having longitudinal and horizontal arms. The horizontal arm has the length of the distance between a first and a second longitudinal welding performed by the L shaped plastic sealing. The diagonally oriented lines can have an obtuse angle in respect of the longitudinal welds. Alternatively, the diagonally oriented lines can have an acute angle in respect of the longitudinal welds. The horizontal weld is applied about every 1 to 20 centimeter along the longitudinal axis of the plastic sheet. The non-welded areas are located about every 5 to 30 centimeter along the longitudinal axis of the inflatable cellular cushioning material. The non-welded areas measure about 0.3 to 3 centimeters.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

5            Fig. 1 is a cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves extending substantially the entire width of the shown sheet, known in the art;

            Fig. 2 is a side view of a device for manufacturing of the cellular cushioning material, in accordance with the present invention.

10           Fig. 3 is a pre-weld cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves and a longitudinal weld, in accordance with a preferred embodiment of the present invention;

            Fig. 4 is a cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves having a horizontal and longitudinal welding, in  
15 accordance with the preferred embodiment of the present invention.

            Fig. 5 is a cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves having a horizontal welding added after air is injected into the inflatable sleeves, in accordance with another embodiment the present  
invention.

20

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves and a horizontal weld is disclosed.

The present invention overcomes the disadvantages of the prior art by providing cellular cushioning material having diagonally oriented inflatable sleeves with a longitudinal weld, either pre-welded or welded during the process of manufacture. The longitudinal weld is placed along the path of the air inlet pipe. Thus, the present invention improves the cellular cushioning material substantially reducing the non-inflatable areas.

The device for manufacturing of the cellular cushioning material in accordance with the present invention is shown in Fig. 2. Device 200 can be used for manufacturing of the cellular cushioning material in accordance with the present invention. Device 200 can be a portable device through which plastic material is fed to create the cellular cushioning material. Any type of plastic or polymer based material can be used in association with the device 200 for manufacturing of the cellular cushioning material. Pre-welded dispensing roll 202 feeds continuous pre-welded plastic sheet 204 through flat plates 206, 208. The pre-welded plastic sheet comprises two layers of plastic or two bi-layer sheets of plastic. In the preferred embodiment, the outer two layers of the plastic sheet are made of thick plastic film resistant to such a degree so it will not melt during the welding process and the inner two layers are made of thinner plastic sheets which would weld together upon the application of heat and the welding bars. Air inlet pipe 210 is connected via an air conduit to air blower 209 or other air or gas supplying device. Air inlet pipe 210 is inserted via a knife (not shown) or other tearing device between the top and the bottom inner layers of the plastic sheet. Air is injected through the air inlet pipe into the plastic sheet thus inflating the diagonally pre-welded sleeves. The plastic sheet now inflated 212 is welded using horizontal bars 214, 216 applying pressure and heat to the inflated plastic sheet, thus providing a welded and inflated cellular cushioning material 218. Other embodiments of apparatuses that can be used are apparatuses depicted in co-filed

PCT application titled INFLATABLE CELLULAR CUSHIONING MATERIAL HAVING A BRICK LIKE FORMATION by Matarasso.

Fig. 3 illustrates the cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves and a longitudinal weld, in accordance with the preferred embodiment of the present invention. In accordance with this  
5      embodiment of the present invention a pre-welded cellular cushioning material 300 is provided. Pre-welded cellular cushioning material 300 comprises diagonally welded sleeves 302, 304, 306 extending from the edges to the center of the plastic sheet allowing for the insertion of air during the process of  
10     manufacture of the cellular cushioning material. The air is inserted by the air inlet pipe 210 as shown in association with the device of Fig. 2. While the edge of the diagonal weld may terminate in a downward position 308 there is still left an opening to allow the inflating of the sleeves. In accordance with the present invention, the cellular cushioning material is also added with at least one  
15     additional weld along the longitudinal path of the air inlet pipe entry line 310.

If the air inlet pipe line is located in the middle of the plastic sheet 300 then two horizontal welds along the entire plastic sheet are added 310, 312. In order to enable the flow of air into the sleeves created by the diagonal lines small non-welded areas 314 along the horizontal path of the plastic sheets must be  
20     maintained.

In accordance with the present invention the diagonal welding forming the sleeves terminate around the mid section of the plastic sheet without connecting to the longitudinal lines along the span of the plastic sheet. When the air flows through the air inlet pipe 210 of Fig. 2 into the plastic sheet, the air  
25     flows from the internal channel 316 created by the horizontal line through non-welded longitudinal line areas 314 to the sleeves created by the diagonal welded lines. In the preferred embodiment of the present invention the non-welded longitudinal line areas 314 are located about every 3 to 30 centimeters along the longitudinal axis of the plastic sheet and measure about 0.3 to 3 centimeters. The  
30     flow of air causes the inflation of the diagonal sleeves. Once the longitudinal



welding is applied to the plastic sheet by the bars 216, 214 of Fig. 2 the area having horizontal welding along the horizontal path is sealed having air there within thus creating the inflated cellular cushioning material thus minimizing the unsealed areas with the exception of the non-welded horizontal line areas 314 and  
5 allowing for less non-inflated areas within the processed cellular cushioning material. The horizontal weld placed by bars 216, 214 is preferably applied to the plastic sheet about every 1 to 20 centimeter along the longitudinal axis of the plastic sheet.

The addition of the welded horizontal lines along the air inlet pipe also  
10 allows for the diagonally lines to be created in various degrees in respect of the longitudinal welds. Thus, an obtuse angle (ranging in the about 110 degrees to the about 160 degrees) or an acute angle (ranging in the about 20 degrees to the about 70 degrees) than the diagonal angle shown in Fig. 3 can be used to create the plastic sheet. In addition, less diagonally oriented lines may be used thus creating  
15 larger sleeves and allowing greater speed in manufacturing the welded plastic sheet.

Fig. 4 shows a cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves having a horizontal and longitudinal welding, in accordance with the preferred embodiment of the present invention.  
20 As seen in Fig. 4 areas 400, 402 are the only non-inflated areas along the plastic sheet. These areas are not inflated because of the remaining non-welded horizontal line areas 314 of Fig. 3. It will be appreciated that the addition of longitudinal welded lines to plastic sheet 300 of Fig. 3 results in a cellular cushioning material having substantially less non-inflated areas along the mid  
25 section of the plastic sheet. Persons skilled in the art will appreciate that the same addition of welded horizontal line along the side of the plastic sheet, in such embodiments where the inlet pipe is inserted and operates at one side of the plastic sheet will likewise result in substantial less non-inflated areas along the plastic sheet..

Reference is now made to Fig. 5 showing a cellular cushioning material having a plurality of diagonally oriented, inflatable sleeves having a longitudinal welding added after air is injected into the inflatable sleeves, in accordance with another embodiment the present invention. On accordance with this alternative embodiment of the present invention the welded horizontal line is added to the plastic sheet during the process of manufacture of the cellular cushioning material. Plastic sheet 500 is a plastic sheet having pre-welded diagonal oriented lines creating sleeves along the length of the plastic sheet. In accordance with the present embodiment extensions of the diagonal welded lines need be performed downward to achieve maximum sealing. The plastic sealing bars 216, 217 of Fig. 2 is adapted such that an inverted or upside down L shaped weld (referred to below as L shaped) can be formed along the air inlet pipe path where the welded diagonal lines end in the middle section of the plastic sheet or at one end of the plastic sheet as the case may be.

Reference is made to Fig. 2B showing the L shaped plastic sealing bars showing an exemplary L shaped welding bars for the use in association with the device shown in Fig. 2 and for manufacturing the cellular cushioning material shown in Fig. 5. The L shaped welding bars 216, 214 create a horizontal weld 502 across the plastic sheet and a longitudinal weld 504 measuring at about the length of the next step where the next horizontal weld 506 is to be created by the plastic sealing system of Fig. 2. The length of the L shaped longitudinal line is dictated by the size of the L shaped downward or forward size of the bar performing the L welding. The same length should be equal to the advancing distance of the plastic sheet such as to form an overlapping seal along the length of the plastic sheet forming a completely sealed and inflated cellular cushioning material. The use of the L shaped longitudinal welding bar is advantageous in that it allows complete sealing of the plastic sheet, apart from the actual air inlet pipe path.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described

hereinabove. Rather the scope of the present invention is defined only by the claims, which follow.

## CLAIMS

I/We claim:

1. An inflatable cellular cushioning material having an air inlet pipe path to be inflated by an inflating device through the use of an air inlet pipe, the inflatable cushioning material comprising at least two layers of plastic pre-welded in such a manner so as to form a substantially diagonally oriented lines forming sleeves or cell structure along the longitudinal axis of the inflatable cellular cushioning material and a substantially longitudinal welded lines along the path of the air inlet pipe, the longitudinal welded lines have non-welded longitudinal line areas to allow for the inflating of the sleeves or sell structure, whereby the longitudinal welded lines substantially reduce the non-inflated areas along the path of the air inlet pipe.
2. The inflatable cellular cushioning material of claim 1 wherein the longitudinal welded lines are pre-welded before the plastic sheet is inflated by the inflating device.
3. The inflatable cellular cushioning material of claim 1 wherein the longitudinal welded lines are welded after the sleeves have been inflated.
4. The inflatable cellular cushioning material of claims 2 or 3, wherein the longitudinal welded lines are welded using an L shaped plastic sealing bars having a longitudinal and a horizontal arms.
5. The inflatable cellular cushioning material of claim 4 wherein the horizontal arm is having the length of the distance between a first and a second longitudinal welding performed by the L shaped plastic sealing.
6. The inflatable cellular cushioning material of claim 1 wherein the inflating device is an air blower.

7. The inflatable cellular cushioning material of claim 1 wherein each one of the two layers of plastic is made of one or more layers of plastic.
8. The inflatable cellular cushioning material of claim 1 wherein plastic is a polymer based material.
9. The inflatable cellular cushioning material of claim 1 wherein the diagonally oriented lines having an obtuse angle in respect of the longitudinal welds.
10. The inflatable cellular cushioning material of claim 1 wherein the diagonally oriented lines having an acute angle in respect of the longitudinal welds.
11. The inflatable cellular cushioning material of claim 1 wherein the horizontal weld is applied about every 1 to 20 centimeter along the longitudinal axis of the plastic sheet.
12. The inflatable cellular cushioning material of claim 1 wherein the non-welded areas are located about every 5 to 30 centimeter along the longitudinal axis of the inflatable cellular cushioning material.
13. The inflatable cellular cushioning material of claim 1 wherein the non-welded areas measure about 0.3 to 3 centimeters.

1/5




FIG. 1




FIG. 2

Best Available Copy

3/5





FIG. 3

Best Available Copy





**FIG.4** Best Available Copy

5/5




FIG. 5

Best Available Copy

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 December 2003 (18.12.2003)


PCT

(10) International Publication Number  
**WO 2003/103929 A3**

- (51) International Patent Classification<sup>7</sup>: **B31D 5/00**,  
B65D 81/05
- (21) International Application Number:  
PCT/IL2003/000476
- (22) International Filing Date: 4 June 2003 (04.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/385,607 5 June 2002 (05.06.2002) US
- (71) Applicant (for all designated States except US):  
NOVA-TEK TECHNOLOGIES, LTD. [IL/IL]; P.O.  
Box 8389, Sapir Industrial Zone, IS-42504 Netanya (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): MATARARSSO,
- (74) Agents: AGMON, Jonathan et al.; Soroker-Agmon, Ad-  
vocates & Patent Attorneys, Nolton House, 14 Shenkar  
Street, 46725 Herzliya Pituach (IL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: AN IMPROVED CELLULAR CUSHIONED MATERIAL



(57) Abstract: An inflatable cellular cushioning material having an air inlet pipe path (316) to be inflated by an inflating device (210) through the use of an air inlet pipe, the inflatable cushioning material comprising at least two layers of plastic cellular cushioning material (300) pre-welded in such a manner so as to form a substantially diagonally oriented lines forming sleeves (302, 304) along the longitudinal axis of the inflatable cellular cushioning material and a substantially horizontal welded lines along the path of the air inlet pipe whereby the horizontal welded lines substantially reduce the non-inflated areas along the path of the air inlet pipe.

WO 2003/103929 A3



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**(88) Date of publication of the international search report:**

13 May 2004

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/IL 03/00476

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B31D5/00 B65D81/05

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B31D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 209 286 B1 (PERKINS ANDREW ET AL) 3 April 2001 (2001-04-03)	1,2,6-10
Y	the whole document	3
Y	FR 1 392 961 A (SUROY JULES LEON) 19 March 1965 (1965-03-19)	3
	the whole document	
A	US 4 096 306 A (LARSON CURTIS L) 20 June 1978 (1978-06-20)	1
	the whole document	
A	DE 38 01 041 A (BECKER ROLF) 27 July 1989 (1989-07-27)	1
	abstract; figure 9B	
	--- -/-- ---	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

25 March 2004

Date of mailing of the international search report

06/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Balz, O

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IL 03/00476

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02 18211 A (ELIACHAR ELIAHU ;LILACH NIR (IL); RAPA RETAIL AIR PILLOW APPLIAN ( ) 7 March 2002 (2002-03-07) the whole document ----	1
P,X	WO 02 055293 A (NOVA TEK TECHNOLOGIES LTD ;RONIPAL LTD (IL); MATARASSO HASDI (IL)) 18 July 2002 (2002-07-18) the whole document -----	1-3,6-9

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 03/00476

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6209286	B1	03-04-2001	AU 3511700 A WO 0053501 A1	28-09-2000 14-09-2000
FR 1392961	A	19-03-1965	NONE	
US 4096306	A	20-06-1978	US 4169002 A	25-09-1979
DE 3801041	A	27-07-1989	DE 3705167 A1 DE 3801041 A1 DE 3861725 D1 WO 8806131 A1 EP 0349542 A1 ZA 8801119 A	01-09-1988 27-07-1989 07-03-1991 25-08-1988 10-01-1990 30-01-1991
WO 0218211	A	07-03-2002	AU 8008001 A WO 0218211 A2	13-03-2002 07-03-2002
WO 02055293	A	18-07-2002	US 2002094393 A1 CA 2434199 A1 EP 1360064 A2 WO 02055293 A2	18-07-2002 18-07-2002 12-11-2003 18-07-2002